

Constants:

$$e = 1.6 \times 10^{-19} \text{C}; \epsilon_0 = 8.85 \times 10^{-12} \text{C}^2/\text{Nm}^2; k = \frac{1}{4\pi\epsilon_0} = 9.0 \times 10^9 \text{N} \cdot \text{m}^2/\text{C}^2$$

Unit conversion:

$$eV = 1.6 \times 10^{-19} \text{J}$$

Formulas

- $\vec{F} = k \frac{q_1 q_2}{r^2} \hat{r}; \vec{E} = k \frac{q_1}{r^2} \hat{r}$ Coulomb's Law
- $\vec{\tau} = \vec{p} \times \vec{E}; U = -\vec{p} \cdot \vec{E}$ Torque and potential energy of an electric dipole in electric field.
- $\Phi_E = \oint \vec{E} \cdot d\vec{A} = \frac{Q_{encl}}{\epsilon_0}$ Gauss's Law
- $V = \frac{1}{4\pi\epsilon_0} \frac{q}{r}$ Electric potential due to a point charge
- $C = \frac{Q}{V}$ Capacitance
- $C_{eq} = C_1 + C_2$ Equivalent capacitance of two parallel connected capacitors
- $\frac{1}{C_{eq}} = \frac{1}{C_1} + \frac{1}{C_2}$ Equivalent capacitance of two series connected capacitors
- $U = \frac{1}{2} QV$ Energy stored in capacitor
- $K = \frac{\epsilon}{\epsilon_0}$ Dielectric constant of a material.
- Relationships among \vec{F} , \vec{E} , U , and V

